


CONNECTION TABLE		
PIN	LEAD COLOR	SIGNAL
1	PURPLE	Y2
2	ORANGE	Y1
3	WHITE	X4
4	BROWN	X3
5	YELLOW	X2
6	GRAY	X1
7	GREEN/WHITE	RX-
8	GREEN	RX+
9	BLUE/WHITE	TX-
10	BLUE	TX+
11	RED	+V
12	BLACK	-V

REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
A	INITIAL RELEASE ECO 7308	9/16/15	M Cole



TERMINAL HOUSING: JST GHR-12V-S OR EQUIV.
 CRIMP JST SSSL-002T-P0.2 OR EQUIV. (12X)

TOLERANCES		THIRD ANGLE PROJECTION		APPLIED MOTION PRODUCTS, INC.	
DECIMALS: MM (INCH) X.XXX = ±0.013 (.005) X.XX = ±0.25 (.01) X.X = ±2.5 (0.1) ANGLES: MACH. = ±.5° CHAM. = ±5°				TSM11 LEAD ASSEMBLY	
COMPUTER DATA BASE DRAWING		APPROVALS DRAWN <i>R.JONEZ</i> CHECKED APPROVED			
				B	DWG NO. 3004-319
					REV A
				SCALE: NTS	SHEET 1